

# Other Metal Fittings...

## DIELECTRIC UNION • FIP x SOLDER

BRASS



- Prevents electrolysis or galvanic action when connecting dissimilar materials
- For use with water up to 210° F
- Threaded ends comply with ANSI B1.20.1
- Solder ends comply with ANSI B16.18

Part No.	UPC-A (032888)	Size	Inner/Master Carton Qty.	Master Weight (Lbs.)
168-003	680036	1/2"	10/100	32
168-003HC	680036	1/2"	30/NA	16
168-004	680043	3/4"	10/100	43
168-004HC	680043	3/4"	30/NA	17
168-094	680944	3/4"x1/2"	10/100	41
168-005	680050	1"	10/80	44
168-005HC	680050	1"	25/NA	14
168-006	680067	1-1/4"	10/40	35
168-007	680074	1-1/2"	5/30	43
168-008	680081	2"	5/20	52

## DIELECTRIC UNION • MIP x SOLDER

BRASS



- Prevents electrolysis or galvanic action when connecting dissimilar materials
- For use with water up to 210° F
- Threaded ends comply with ANSI B1.20.1
- Solder ends comply with ANSI B16.18

Part No.	UPC-A (032888)	Size	Inner/Master Carton Qty.	Master Weight (Lbs.)
167-003HC	670037	1/2"	25/NA	11
167-004	670044	3/4"	10/100	61
167-004HC	670044	3/4"	50/NA	24
167-094	670945	3/4"x1/2"	10/100	61

## DIELECTRIC UNION • FIP x FIP

GALVANIZED x GALVANIZED



- Prevents electrolysis or galvanic action when connecting dissimilar materials
- For use with water up to 210° F
- Threaded ends comply with ANSI B1.20.1

Part No.	UPC-A (032888)	Size	Inner/Master Carton Qty.	Master Weight (Lbs.)
165-003	650039	1/2"	10/100	50
165-004	650046	3/4"	10/100	68
165-005	650053	1"	5/50	54
165-006	650060	1-1/4"	5/40	60
165-007	650077	1-1/2"	5/30	93
165-008	650084	2"	2/20	79

## DIELECTRIC UNION • FIP x BRASS PIPE

GALVANIZED x BRASS



- Prevents electrolysis or galvanic action when connecting dissimilar materials
- For use with water up to 210° F
- Threaded ends comply with ANSI B1.20.1

Part No.	UPC-A (032888)	Size	Inner/Master Carton Qty.	Master Weight (Lbs.)
165-103	651036	1/2"	10/100	52
165-104	651043	3/4"	10/100	70
165-105	651050	1"	5/50	38

# M

MADE IN TAIWAN